



Effects of pumping strategies on pesticide concentration of a drinking water well

Aisopou, Angeliki; Binning, Philip John; Bjerg, Poul Løgstrup; Albrechtsen, Hans-Jørgen

Publication date:
2011

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Aisopou, A., Binning, P. J., Bjerg, P. L., & Albrechtsen, H-J. (2011). *Effects of pumping strategies on pesticide concentration of a drinking water well*. Abstract from 2011 AGU Fall Meeting, San Francisco, CA, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

ABSTRACT FINAL ID: H41B-1034

TITLE: Effects of pumping strategies on pesticide concentration of a drinking water well

SESSION TYPE: Poster

SESSION TITLE: H41B. Agricultural Surface and Groundwater Quality I Posters

AUTHORS (FIRST NAME, LAST NAME): Angeliki Aisopou¹, Poul Løgstrup Bjerg¹, Philip J Binning¹, Hans-Jørgen Albrechtsen¹

INSTITUTIONS (ALL): 1. DTU (Technical University of Denmark), Kgs. Lyngby, Denmark.

Title of Team:

ABSTRACT BODY: Groundwater is an important source of drinking water production in many countries including Denmark. This requires high quality groundwater that meets the standards of the European Water Framework Directive. Yet as a result of agricultural activity, deposition and previous handling, pesticides are frequently found in groundwater and can raise a substantial problem for ground water abstraction. The concentration of this contamination may vary between different layers. The heterogeneity of the subsurface geology and the depth of the drinking water well's screen are important parameters that affect the resulting contamination of the abstracted groundwater. The pesticide concentration in wells may also be affected by the pumping strategy because pumping can alter the structure of the flow field, the flowpath of water going to the well and subsequently the age of water at the well.

The purpose of this study was to examine numerically the effects of pumping on pesticide contamination of drinking water wells using a reactive transport model in a hypothetical aquifer system resembling a typical Danish well field. The application history of the pesticides is crucial. This can be taken into account by assessing the effects of pumping on water age distribution along the well.

Three compounds with different application histories were considered: an old banned pesticide MCP (Mecoprop) which is mobile and relatively persistent in deeper aquifers, and a highly applied, biodegradable and strongly sorbing pesticide glyphosate, and its degradation product AMPA. A steady state flow field was first computed. A well field was then introduced and different pumping regimes were applied for a period of 180 years; a low-rate pumping, a high-rate pumping and a varying pumping regime. A constant application rate at the surface was assumed for the application period of each pesticide. The pre-abstraction age distribution of the water in the system was first estimated using a steady-state flow and transport simulation. These water ages were then used as the initial conditions for the transient simulations.

The results of the simulations showed that the range of water ages contributing to the well increased during pumping and was substantially affected by the pumping rate. High pesticide concentrations were persistent in the well 40 to 100 years after they were banned, due to the high residence times in the aquifer. Large changes in simulated pesticides concentrations at the well occurred during pumping. The pesticide concentration reaching the well was affected by the pumping regime and the pesticide application history and properties. A higher pumping rate induced a higher pesticide concentration peak at the well of shorter duration, while a lower pumping rate induced a lower concentration peak of longer duration. The long term scenarios revealed that at high pumping rates MCP would disappear 40 years after its application end year, while glyphosate concentrations increase and reach a plateau, which is

highly dependent on the pumping rate. The findings of the study help understand the results of groundwater monitoring programmes and can be used for the quantitative evaluation of management and pumping strategies for the long-term supply of safe potable groundwater.

KEYWORDS: [1803] HYDROLOGY / Anthropogenic effects, [1847] HYDROLOGY / Modeling, [1831] HYDROLOGY / Groundwater quality.

(No Image Selected)

(No Table Selected)

SPONSOR NAME: Philip Binning

Additional Details

Previously Presented Material:

Contact Details

CONTACT (NAME ONLY): Angeliki Aisopou

CONTACT (E-MAIL ONLY): agea@env.dtu.dk
